



TinyChem
Specialities Pvt. Ltd.
Formulators of Performance Additives

DEFOAM C LIQUID

Oil Well Cement Slurry & Adhesives

Construction, Adhesives

Typical chemical and physical Properties

DEFOAM C Liquid is an effective antifoaming agent for Oil Well Cement Slurries. It is particularly designed to eject entrained air from organic admixtures. It is also used in making polyvinyl alcohol – based clear adhesives as it does not impart haze to the final product.

PROPERTIES:

Appearance	Pale Yellow viscous clear liquid
Active Content	100%
Dispersibility / Solubility	Dispersible in water
pH	7 ± 1.0

Applications and typical treat level recommended

DEFOAM C LIQUID can be easily added / blended into admixture formulations. Recommended level of addition is approx. 0.08% to 0.14% of total weight to remove and control the entrained air in the given system.

Benefits

DEFOAM C Liquid reduces entrained air without changing slurry Properties. Recommended dosage level is 0.06% to 0.12% by Weight of the water, eliminates entrained air in most systems.

The minimum dosage required will depend upon the organics which are present. DEFOAM C Liquid will eliminate entrained air, which causes problem in Pumping, Troweling and complete cavity filling. It will also prevent excessive shrinkage, porosity and weakness of the set cement.

Disclaimer:

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.

Regd. Office :
#24 - North, 2nd Floor,
Jaybharat Society, 3rd Road, Khar (W),
Mumbai - 400 052. INDIA
Tel : 91-22-2648 3153 / 2648 5368

Works :
J/2315, 11th Phase, G.I.D.C.,
Vapi - 396 195 (Gujarat) INDIA
Tel.: 91-260-242 0474, 242 1399

E-mail : info@tinychem.com
Website : www.defoamingagents.com