



Paints, Coatings & Adhesives

Typical chemical and physical Properties

TICOL DPV is a 99.9% active defoamer for paints and adhesives based on polyvinyl acetate emulsions. It is also a versatile defoamer in manufacturing of glues and a few other applications where compatibility to a particular system is critical.

A Blend of Petroleum derivatives with proprietary additives

PROPERTIES:

Appearance	Light amber liquid
Solubility	Dispersible in water
Cloud Point (deg.C)	< 10
pH (2% solution)	6.5
Moisture	1% Max.

Applications and typical treat level recommended

Paints and Adhesives
Always stir well before use. 0.2% to 1% of weight of PVA Emulsion or any similar foaming media.

TICOL DPV is recommended for use as it is and not in any kind of diluted form.

Benefits

TICOL DPV is a 99.9% active product and performs exceedingly well in controlling foam generation in coating systems based on polyvinyl acetate emulsion.

It protects the appearance and wearing qualities of paint by preventing occurrence of foam during paint production or application.

The other benefits of **TICOL DPV** are:

- ✓ Effective in low pH systems
- ✓ Does not affect colour development
- ✓ It is totally silicone-free hence, no fish eyes or crater formation.

Disclaimer:

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.