



Cement / Asbestos Roofing sheets

Typical chemical and physical properties

TICON 0148 is an organic defoamer especially formulated for the production of cement / asbestos roofing sheets manufacturing process, where foaming is generally observed when cement slurry contains fly ash or pulp.

Combination of fatty alcohols and esters

Properties:

Appearance	Yellowish Liquid
Active content	100 %
Specific gravity at 25 °C	0.88- 0,92 g/cm ³
Viscosity at 25 °C	50-250 mPa.s
Flash Point	> 220 °C

Applications and typical treat level recommended

Dosage 150 - 350ppm

Apply the product in its natural state by aspersion or by dosing pump and adjust the initial dosage according to the requirements.

TICON 0148 may also be distributed with a water dilution system and or with a special metering system for automatic dosing in the fermentation, which means product will automatically added only when needed.

Benefits

TICON 0148 is a 100% active product and shows excellent performance in the control of foams and improves the flow and reduces viscosity of the medium.

It leaves no residues in the pipes or valves of the equipment used.

TICON 0148 is completely biodegradable and non toxic to aquatic life.

Disclaimer:

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.