



TICON HD 30

Foam Control Agent

Cement / Asbestos Roofing sheets

Typical chemical and physical properties

TICON HD 30 is an organic defoamer especially formulated for the production of cement / asbestos roofing sheets.

Combination of vegetable fatty acids, waxes and proprietary additives

Properties:

Appearance	Pale Yellow thick paste
Active content	30 %
Specific gravity at 25 °C	0..92 – 0.98g/cm ³
pH	8 ± 1
Solubility	Water dispersible

Applications and Dosage typical treat level recommended

150 - 350ppm (pre-dilution)

TICON HD 30 can be diluted with water in a ratio of 1:3 to form a ready dispersion that can be added to the foaming media for quick control of foaming in the slurry tank.

Benefits

TICON HD 30 is a 30% active product and shows excellent performance in the control of foams in a media enriched with fly ash and newsprint pulp.

Disclaimer:

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.